

# MAX-N100

Intel® Alder Lake N based Ultra-compact Mini-PC  
with dual HDMI and direct AC power, no adapter needed



## Features

- CPU: Intel® Alder Lake N series Processor
- Memory: Single Channel SO-DIMM DDR4 up to 16GB
- Display: Integrated Intel UHD Graphics display via 2xHDMI
- I/O Ports: 2xLAN, 3xUSB3.2, 1xUSB2.0
- Ethernet: 10/100/1000Mbps
- Storage: 1x M.2 2280 NVMe(PCIe3.0 4X)/SATA, 1xM.2 2280 NVMe(PCIe3.0 1X)
- Power: AC\_JACK(100-240V)

## Introduction

Introducing the MAX-N series Plug-in-Ready ultra-compact mini PC powered by the Intel® Alder Lake N series processor, designed to deliver efficient performance in a small form factor. It is powered directly through an AC jack, eliminating the need for a bulky power adapter and adding to its convenience and ease of use. This new cost-effective mini pc equipped with a quad-core N100 CPU running up to 3.40GHz ensures smooth multitasking and responsive computing. It features 16GB of single-channel DDR4 memory, integrated Intel® UHD Graphics, and dual HDMI ports, which are ideal for dual-display setups.

The MAX-N Series offers versatile I/O options and advanced active cooling solutions and supports Windows and Linux operating systems. It can be the perfect choice for users seeking a powerful yet space-saving computing solution. It features two M.2 slots for SSDs, one additional M.2 slot for WiFi & Bluetooth modules for expansion, and dual Gigabit Ethernet ports for reliable network connectivity. It supports a wide operating temperature range, ensuring stability even in challenging environments with active cooling.



H/W Monitor



Watchdog



## I/O Interfaces



## Technical Specifications

Processor	CPU	N100
	Total Cores/Threads	4C/4T
	Max Turbo Frequency	3.40GHz
	Cache	6MB
	Processor base Power	6W
Memory	Type	Single Channel SO-DIMM DDR4-3200MHz
	Max Capacity	16GB
Display	GPU	Integrated Intel® UHD Graphics
	Display Interface	2xHDMI
Ethernet	Speed	10/100/1000Mbps
	Controller	RTL8111H
	Interface	2xRJ-45
	Wake on LAN	Yes
Audio	Audio Codec	Realtek HD
	Interface	1xCTIA 2-in1 Audio Jack, Supports Line-out+Mic-in
Hardware	CPU temperature, System temperature, Onboard voltage, Watchdog	
Storage	M.2	1xM.2_2280 Slot for NVMe(PCIe3.0 4X)/SATA SSD
	M.2	1xM.2_2280 Slot for NVMe(PCIe3.0 1X) SSD
Expansion	M.2	1xM.2 2230 Slot for WiFi and Bluetooth.
Other I/O	USB2.0	1
	USB3.2	3
Dimension	LED Light Indicator	1(Power_on Light Indicator. Status: White Light)
	Size	120mm x 120mm x 35.5mm (L x W x H)
Power	Standard Port	AC_Jack
	Voltage	Input:100-240V~, 50/60Hz,1.5A, Output: 12V/3.75A
Temperature	Operating Temp.	-10°C to 45°C
	Storage Temp.	-20°C to 60°C
Cooling	Active	
Operating System	Win10/11 64bit, Linux 64bit	

Copyright © 2024 Maxtang Technology Co., Ltd. All rights reserved. All data is for information purposes only and not guaranteed for legal purposes. Information has been carefully checked and is believed to be accurate however, no responsibility is assumed for inaccuracies. Maxtang and the Maxtang logo and all other trademarks or registered trademarks are the property of their respective owners and are recognized. The terms HDMI, HDMI High-Definition Multimedia Interface, HDMI Trade dress, and HDMI Logos are trademarks or registered trademarks of HDMI Licensing Administrator, Inc.

\*All specifications and photos are subject to change without notice.